

2023 KDDA Mild Build full size Truck guideline

- (a) Any year single rear wheel truck, sport utility vehicle allowed.
- (b) 4 wheel drive must be inactive.
- (c) Roof sign with minimum 18" number using contrasting colors.
- (d) Hoods may be fastened in a maximum of 6 places, 2 of these attachment points may go through the frame using no larger than 1" all thread. Chain must not exceed 3/8" link using (1) loop or (2) loops when using a maximum of #9 wire.
- (e) Hoods must have a minimum of (2) non blocked 6" access holes.
- (f) Beds may be fastened no more than 6 places, Tailgates may be secured in 6 places, if mounting the tailgate to the frame this will count as bed mounts.
- (g) Doors must be secured using bolts, chains or welds.
- (h) Any OEM car bumper may be reinforced as long as all added material stays within the bumper. Isolators or brackets in the stock position may be used if the vehicle came with them. Bumpers may be welded using no additional materials. Bumpers may be substituted with a 4" x 4" 3/16" box tubing as clarified in Kdda 2023 build rules (Article II)
- (i) Engine swaps are allowed. Engine mounts may be welded to the frame, while not reinforcing the vehicle. Stock trans crossmembers may be substituted for material not to exceed 2" x 2" x 1/4" wall.
- (j) Outside door bars, window openings, dash bar, spreader bars, uprights, gas tank, and battery box must follow Kdda current build rules (Article IV)
- (K) Stock appearing rear ends (no bracing) from that vehicle class must be used, differentials may be locked. Rear axle humps may be chained in no more than (2) points using one loop.
- (L) Stock steering and tie rod components may be strengthened. Steering U-joints may be added connecting the steering column to the steering box.
- (M) Modified shifters, pedal assemblies, and slider drive shafts may be used.
- (N) Lower engine cradles may be used as long as they are not reinforcing the truck.
- (O) Rear of the vehicle can be pre-bent, side panel body forming will be allowed. wedging of the bed between the rear axle and rear bumper will be allowed.
- (P) You may cut, notch or remove any additional parts to the standard prep rules.
- (Q) Tires and wheels must follow Kdda guidelines. (2023 build rules section 2.04)
- (R) Repairing your vehicle. Kdda 2023 build rule 2.06 (repairing your vehicle)
- (S) Vehicles must follow Kdda 2023 build rule 2.01 (what must be removed)
- (T) IF IT DOES NOT SAY THAT YOU CAN, THEN ASSUME THAT YOU CAN'T.